

SIZES	
IG thickness	7/8"
Height range	12" to 68"*
Width range	8" to 54"*
Size increments	1/16" (height & width)
Max IG size	Max 9 sq. ft. (no more than 36" in one direction)
MATERIALS	
Spacer	Intercept®, tin plated steel
Glass (std.)	1/8" annealed glass or 1/8" tempered safety glass
Glass (Low-E)	1/8" annealed glass or 1/8" tempered safety glass Single Low-e: 2nd surface soft coat (270, 272, 340, 366) Dual Low-E: 4th surface hard coat Low-E (I89)
Glass (NEAT)	Low-E: 1st surface (270 & 366)
Blind slat	11.5mm wide aluminum UV stabilized coating
Sealant	Dual seal equivalent
Desiccant	Desiccant matrix (moisture and chemical management)
Decorative cover caps	UV stabilized, heat tolerant polymer
CODE COMPLIANCE	
IGCC (seal)	ASTM E2190 seal certification
ANSI (glass)	ANSI Z97.1 safety glazing (Applies to tempered glass only)
ASTM (glass)	ASTM C1036-16 (annealed) & C1048-12 (tempered)
ENERGY STAR®	Will help your window achieve ENERGY STAR® performance when select Low-E glass is employed
NFRC	CAD available for simulations
OPERATION	
Single operator	Tilt only
Capillary tube	Do not block, crush or cut
Operator position	Top right (next to ladder cord)
COLORS	
Blind slat	White, Tan, Sand, Espresso, Silver Moon, Slate Gray
Operator	White, Tan, Sand, Espresso, Silver Moon, Slate Gray
Decorative Cover Caps	White, Tan, Sand, Espresso, Silver Moon, Slate Gray
Sealant	Gray
MAINTENANCE	
Clean glass with soap and water or quality window cleaner, as needed	
WARRANTY	
10 year full warranty	

*Please see size charts for size capabilities. Contact your sales representative for size charts.



Parents for Window Blind Safety created the Seal of Approval program over a decade ago, to inform consumers of products which have greatly reduced or completely eliminated the risk of injury to children or pets.



1.866.472.0042 Toll-Free
www.BlinkODL.com

TECHNICAL DRAWING

